

2.1.6.2.1 DELTA PLC Programmable Logic Controller เดลต้า รุ่น EH2



EH2 series is well equipped with outstanding operational speed, large programming capacity and built in application and communication instructions, multiple special extension modules and function cards, enabling the efficiency of the MPU to be utilized to its fullness.

ประเภทสินค้า : **PLC, Delta**

Series: **DVP-EH2 series**

การใช้งาน

High-speed 3-axis servo welding machine, high-speed cutting machine, bar feeder, distributed monitor system in production line.

ขนาดที่มีให้ใช้ : **MPU points: 16 / 20 / 32 / 40 / 48 / 64 / 80**

ข้อมูลทางเทคนิค

Specifications

- Max. I/O points: 512
- Program capacity: 16K Steps
- Instruction execution speed: 0.24 μ S (basic instruction)
- Communication port: Built-in RS-232 and RS-485, compatible with MODBUS ASCII / RTU communication protocol
- Data register: 10,000 words
- File register: 10,000 words
- High-speed pulse output: 20-point and 32-point models support 2-point 200KHz pulse output (Y0, Y2); 40-point models support A/B phase 200KHz pulse output (Y0, Y1)(Y2, Y3) and 2-point 200KHz pulse output (Y4, Y6).
- Built-in 4 groups of hardware high-speed counters